



Karakteristike

Twin KPL vazdušna zavesa

- Specially designed to be installed on doors of industrial cold stores and freezers with big temperature differences.
- The Twin Kool air curtain system has been designed to offer a versatile solution for any type of cold room. It has two jets of opposing air chambers that create additional space between the chamber and the pre-chamber. Thanks to the double barrier, this model becomes the perfect alternative to the TRIOJET SYSTEM air curtain when space is limited or this model is not an option.
- Konstrukcija samoodrživog ku?išta napravljena od galvanizovane ?eli?ne plo?e, završeno u strukturalnoj epoksi-poliester slikarskoj belo? boji RAL9016 kao standardnoj.Druge boje ili nderjaju?i ?elik su dostupne na zahtev.
- Velika brušena ulazna rešetka koja ne zahteva intenzivno održavanje.
- Anodizirani aluminijumski ispusni kraci, aerodinami?nog oblika., prilagodjivi od 0 do 15 stepeni svake strane.
- Centrifugalni ventilatori sa duplim otvorom pokretani spoljašnjim motorom rotora, sa niskim nivoom buke. Selektor 5 brzina.EC modeli sastavljeni sa veoma štedljivim i efikasnim ventilatorima.
- "A" tip bez grejanja, samo vazduh.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 7m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
 - Auxiliary temperature sensors that improve air curtain control and increase energy savings.
 - Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.
- Includes varnishing on the PCB to protect it from corrosion.

Specifikacije

50Hz

Negrejano		
Model	(m²/h)	(m)
TWIN KPL M 1500 A	9,8-13,1	
TWIN KPL M 2000 A	9,8-13,1	
TWIN KPL M 2500 A	9,8-13,1	
TWIN KPL M 3000 A	9,8-13,1	
TWIN KPL ECM 1500 A	9,8-13,8	
TWIN KPL ECM 2000 A	9,8-13,8	
TWIN KPL ECM 2500 A	9,8-13,8	
TWIN KPL ECM 3000 A	9,8-13,8	
TWIN KPL G 1500 A	9,8-13,1	
TWIN KPL G 2000 A	9,8-13,1	
TWIN KPL G 2500 A	9,8-13,1	
TWIN KPL G 3000 A	9,8-13,1	
TWIN KPL ECG 1500 A	9,8-13,8	
TWIN KPL ECG 2000 A	9,8-13,8	
TWIN KPL ECG 2500 A	9,8-13,8	
TWIN KPL ECG 3000 A	9,8-13,8	

60Hz

Negrejano



Model	(m³/h)	(m)
TWIN KPL ECM 1500 A	9,8-13,8	
TWIN KPL ECM 2000 A	9,8-13,8	
TWIN KPL ECM 2500 A	9,8-13,8	
TWIN KPL ECM 3000 A	9,8-13,8	
TWIN KPL ECG 1500 A	9,8-13,8	
TWIN KPL ECG 2000 A	9,8-13,8	
TWIN KPL ECG 2500 A	9,8-13,8	
TWIN KPL ECG 3000 A	9,8-13,8	

Dimenzije

Twin KPL vazdušna zavesa - Dimenzije